

A Kertészeti és Élelmiszeripari Egyetem KÖZLEMÉNYEI

ÉVFOLYAM
1996
(VOL. LV.)

PUBLICATIONES Universitatis Horticulturae Industriaeque Alimentariae

ADIUVANTIBUS:

I. Balogh-Ormos, J. Bernáth
A. Fekete, Á. Hoschke
Z. Láng, P. Lévay, G. Lugosi,
T. Jankovich, É. Zalai-Kovács,
G. Schmidt, G. Szabó

REDIGIT:

Pál Sass

BUDAPEST, 1996

This periodical is a publication
of the University of Horticulture
and Food Industry, Budapest,
Hungary.

For information concerning other
publications of University,
including exchange possibilities,
please contact the Exchange Section
of the University Central Library,
Villanyi út 35-43
H-1118 Budapest, Hungary
Phone: (36-1) 166-6020
Fax:(36-1) 166-6020

EDITOR:
Gábor Schmidt

SECRETARY OF EDIT. BOARD:
Éva Zalai-Kovács

RED. TECHN.
Eszter Batiz
Zsolt Szafián

Reviewers:

Jenő Bernáth
Erzsébet Jámbor-Benczúr
Géza Faeser
András Fekete
Péter Fodor
Edit Forró
Károly Hrotkó
Kornél Korány
Annamária Mészáros
Erika Békássy-Molnár
Mária Lujza Reményi
Gábor Schmidt
József Szalai

Contents - Tartalomjegyzék**FOOD INDUSTRY**

Cecilia Hodúr, Róbert Rajkó, Gábor Szabó:	
MEASURING OF HAZE BY FILTRATION	5
Róbert Rajkó, Cecilia Hodúr, Gábor Szabó:	
ON THE SENSITIVITY INVESTIGATION OF A ROTATING FILM EVAPORATOR BY TAGUCHI'S EXPERIMENTAL DESIGN METHODOLOGY	9
István Pais, Tibor Tóth:	
THE HUMAN PALEONUTRITION IN CARPATHIAN BASIN FROM NEOLITHIC TO MEDIEVAL TIMES BASED ON OSTEOCHEMICAL ANALYSIS (SHORT COMMUNICATION)	15
Pál Sass, Tünde Lovász, Péter Merész, Péter László, János Zana:	
SOME EXPERIMENTAL RESULTS AND PERSPECTIVES IN IMPROVING TEXTURE AND PRODUCT QUALITY OF HUNGARIAN APPLE CULTIVARS	20
András S. Szabó, K. Heydorn, E. Damsgaard, Péter Fodor:	
DETERMINATION OF VANADIUM IN PLANT SAMPLES USING A NONDESTRUCTIVE AA TECHNIQUE AND AN ICP-AES METHOD	28

HORTICULTURE

Eszter Batiz, Elisabeth Jámbor-Benczúr:	
IN VITRO PROPAGATION AND ACCLIMATIZATION OF <i>MICROSORUM PUNCTATUM 'GRANDICEPS'</i> ..	33
Géza Fácsar:	
NATURE CONSERVATION VALUE OF NATIVE ROSA SPECIES AND NATURE CONSERVATION PRACTICE IN HUNGARY	38
Mohamed Gad, Gábor Schmidt, László Gerzson:	
GROWTH RETARDANTS AFFECT THE LEAF CHARACTERISTICS OF SOME ORNAMENTAL PLANTS ..	48
László Gerzson, Mohamed Gad:	
EFFECTS OF GROWTH RETARDANTS ON GROWTH AND FLOWERING OF <i>PETUNIA HYBRIDA</i> JUSS. AND <i>TORENIA FOURNERI</i> L.	60
László Hargitai:	
SOME ASPECTS OF THE ORGANOPHILITY AND HYDROPHILITY OF TOXIC HEAVY METALS BY SOIL CONTAMINATION	66
Péter Lévai:	
POSSIBILITIES OF USING FRAMELESS PLASTIC COVER IN ORNAMENTAL PLANT GROWING ..	75
József Nagy:	
LIST OF PROTECTED PLANTS OF THE CENTRAL BÖRZSÖNY MOUNTAINS	80
Ramadan Fouda:	
ANATOMICAL STRUCTURE OF STEM IN THE ABOVE- AND UNDERGROUND PORTIONS OF <i>ROSA SPINOSISSIMA</i> L. SUCKERS	84
Gábor Schmidt, Ramadan Fouda	
HISTOLOGICAL STUDIES ON THE ABOVE - AND UNDERGROUND STEM OF <i>PRUNUS TENELLA</i> (<i>SYN. AMYGDALUS NANA</i>) 'KATT' SUCKERS	89
Béla Timon:	
TRAINING OF PEACH TREES TO SLENDER SPINDLE IN HUNGARY	94

LANDSCAPE ARCHITECTURE

Kristóf Fatsar:	
CONTRADICTIONS IN THE INTERPRETATION OF AUTHENTICITY IN CONNECTION WITH THE CONSERVATION OF MONUMENTS OF DIFFERENT TYPES	98
Krisztina Kincses:	
RECLAMATION OF ABANDONED SURFACE MINES	102

ON THE SENSITIVITY INVESTIGATION OF A ROTATING FILM EVAPORATOR BY TAGUCHI'S EXPERIMENTAL DESIGN METHODOLOGY

Róbert Rajkó, rajko@sol.cc.u-szeged.hu

Cecilia Hodúr,

Gábor Szabó, fotit@szef.u-szeged.hu

Department of Unit Operations and Food Processing

University College of Food Industry

H-6701 Szeged, POB 433, Hungary

Tel.: + 3662 456030, Fax: + 3662 456034

1. Introduction

The separation of a solvent from a solution of a solvent and a nonvolatile solute is commonly effected by use of the unit operation known as evaporation. Since energy is transferred in an evaporator from a condensing vapor to a boiling liquid, evaporation may be regarded as a special case of the unit operation called heat transfer [1,2,3,4]. Evaporators are commonly found in the inorganic, organic, paper, and sugar industries. Typical applications include the concentration of sodium hydroxide, brine, organic colloids, and fruit juices. Generally, the solvent is water.

Based on the previous investigations of the rotary film evaporator type UNIFILM with 0.3 m^2 heating surface designed and settled by CHEMIMAS for our department [5,6], we have critically investigated of the equipment to find optimal operational parameters (as factors) by experimental design [7,8].

2. The equipment

The experiments have been performed with a direct-flow falling, concurrent, underdriven rotating film evaporator with swinging blade (see Fig. 1).

3. Experimental design for optimization

For the first experiments, water was used as model material. We created a replicated 2^{5-1} fractional factorial design for 5 factors (steam pressure as z_1 , vacuum as z_2 , revolutions per minute as z_3 , volume flow rate of cooling water as z_4 , volume flow rate of feed as z_5), the optimisation parameter was chosen the mass flow rate of vapor in percent of the feed. The results can be seen in Table 1.




Figure 1 - UNIFILM-type rotating film evaporator
1-1a. bearing, 2. case, 3. rotor, 4. vapor separator, 5. holder and driving

Table 1. The results of the fractional factorial design

steam pressure <i>Z₁</i> kp/cm ²	vacuum <i>Z₂</i> kp/cm ²	revolutions per minute <i>Z₃</i> 1/min	volume flow rate of cooling water <i>Z₄</i> litre/min	volume flow rate of feed <i>Z₅</i> litre/h	mass flow rate of vapor in percent of feed y %	mass flow rate of liquid in percent of feed %
2.8	0.6	3900	40	120	26.3±0.6	73.7±1.4
3.8	0.6	3900	40	80	51.3±1.1	48.7±3.7
2.8	0.8	3900	40	80	39.2±1.1	60.8±2.9
3.8	0.8	3900	40	120	36.5±0.7	63.5±1.5
2.8	0.6	4700	40	80	39.2±0.6	60.8±0.4
3.8	0.6	4700	40	120	27.5±0.6	72.5±0.8
2.8	0.8	4700	40	120	27.0±1.6	73.0±2.5
3.8	0.8	4700	40	80	54.5±0.3	45.5±0.6
2.8	0.6	3900	60	80	34.7±2.9	65.3±2.9
3.8	0.6	3900	60	120	25.1±0.5	74.9±0.6
2.8	0.8	3900	60	120	29.4±0.6	70.6±0.6
3.8	0.8	3900	60	80	51.7±0.7	48.3±1.2
2.8	0.6	4700	60	120	22.5±0.6	77.5±0.9
3.8	0.6	4700	60	80	46.1±1.2	53.9±0.5
2.8	0.8	4700	60	80	47.5±5.1	52.5±7.4
3.8	0.8	4700	60	120	34.3±0.7	65.7±2.2

The following linear function was fitted to the data:

$$y = 37.05 - 8.48 z_1 - 0.64 z_2 + 0.26 z_3 + 2.98 z_4 + 3.82 z_5 \quad (1)$$

The determination coefficient is 0.9246, and the F-value equals 24.53 and this value is significantly larger than $F(5,10)_{0.01} = 5.63$, even larger than $F(5,10)_{0.05} = 3.32$, so the linear function is adequate. According to Eq. 1, we have created the gradient design, the final step to find the optimum. See the results in Table 2 and Fig. 2.

Table 2. The results of the gradient design

	steam pressure z_1 kp/cm ²	vacuum z_2 kp/cm ²	revolutions per minute z_3 1/min	volume flow rate of cooling water, z_4 litre/min	volume flow rate of feed z_5 litre/h	mass flow rate of vapor in percent of feed, y %	mass flow rate of liquid in percent of feed %
1	3.6	0.74	4300	50	77	45.9±0.6	54.1±1.4
2	3.6	0.75	4300	50	69	54.1±0.8	45.9±0.8
3	3.7	0.77	4300	50	61	61.5±0.6	38.5±1.3
4	3.8	0.78	4300	50	53	80.4±2.8	19.6±8.2
5	3.9	0.80	4300	50	46	86.3±2.1	13.7±4.0




Figure 2 - The graph of the gradient design

4. Sensitivity investigation

In the second part of our investigation we try to obtain the sensitivity (9,10) of the evaporation to the factors. The model material was chosen as mixture of water, sugar and ascorbic acid as model material. Ascorbic acid was used for indicate whether the heat effect was harmful to the model materials. We did not find any changes in the amount of ascorbic acid after evaporation, so the evaporation was considerate enough.

For our rotating film evaporator, the following factors can be considered:

Controllable factors

steam pressure

vacuum

revolutions per minute of rotor

volume flow rate of cooling water

volume flow rate of feed

concentration of the sugar

Noise Factors

Internal

aging of the equipment materials

External

quality of the steam

temperature and flow of the air as surroundings

temperature of the cooling water

steam-trap valve

Individually fluctuation

equipment operator person

We chose only three controllable factors, i.e., the steam pressure, the vacuum and the concentration of the sugar. Fig. 3 shows the outline of the created 2^{3-1} fractional factorial design and the results can be seen in Table 3.




Figure 3. Outline of the 2^{3-1} fractional factorial design for Taguchi methodology

Table 3. Results of the 2^{3-1} fractional factorial design

steam pressure	vacuum	revolutions per minute	volume flow rate of cooling water	volume flow rate of feed	concentration of the sugar	mass flow rate of vapor in percent of feed
Z_1 kp/cm ²	Z_2 kp/cm ²	Z_3 1/min	Z_4 litre/min	Z_5 litre/h	Z_6 g/100g	y %
3.8	0.785	4300	50	55	9.5	
0.05	0.005	0	0	0	0.5	
3.85	0.79	4300	50	55	10	74.20±0.64
3.85	0.78	4300	50	55	9	72.53±0.62
3.75	0.79	4300	50	55	9	74.34±1.0
3.75	0.78	4300	50	55	10	72.50±1.3
(+) 73.36	(+) 74.27					(+) 73.35
(-) 73.42	(-) 72.51					(-) 73.43
-0.06	1.75					-0.08

Sensitivity calculations for:

steam pressure:

$$(74.20+72.53)/2 - (74.34+72.50)/2 = -0.06,$$

vacuum:

$$(74.20+74.34)/2 - (72.53+72.50)/2 = 1.75,$$

concentration of the sugar:

$$(74.20+72.50)/2 - (72.53+74.34)/2 = -0.08.$$

5. Conclusions

When water used as model material for optimization, the results coming from gradient design show us that there is no sharp optimal region of factor values, so we have to put these values depending on the technological purpose and materials used for it. The most influential factors are the steam pressure, vacuum, and the volume flow rate of feed.

We have also investigated the rotating film evaporator with Taguchi methodology, which is emphasized the use of fractional designs and other orthogonal arrays with objectives of making products robust to environmental conditions, making products insensitive to component variation, minimizing bias and mean square error about specification values, and reliability and life testing.

We have used mixture of water, sugar and ascorbic acid as model material and the results show us that the evaporation is the most sensitive to the vacuum. Since the evaporation is insensitive to the steam pressure, we can set it to the lower value to execute the operation more economically. The fact, that small change (about 1%) in the concentration of the sugar is not influential too, is reassuring.

Acknowledgement

R. Rajkó would like to thank the support of MHB "A Magyar Tudományért" Alapítvány.

References

1. Pallai, I. and Fonyó, Zs. (Eds.): *Studies in Computer-Aided modelling, Design and Operation, Part A: Unit Operations*, Akadémiai Kiadó, Budapest 1992
2. Hetsroni, G. (Ed.): *Handbook of Multiphase Systems*, McGraw-Hill, New York, 1982
3. McCabe, W.L. and Smith, J.C.: *Unit Operations of Chemical Engineering*, McGraw-Hill Kogakusha, Tokyo, 1976
4. Holland, C.D.: *Fundamentals and Modeling of Separation Processes: Absorption, Distillation, Evaporation, and Extraction*, Prentice-Hall, Englewood Cliffs, New Jersey 1975
5. Sárosi, H.; Papp, T. and Hotya, Zs.: Capacity increase with rotary film evaporating (in Hungarian), *Élelmiszeripari Főiskola, Tudományos Közlemények*, 19, 1994, 69-76
6. Sárosi, H.; Papp, T. and Molnár, L.: Possibilities of the production of export quality concentrates made with rotating film-evaporator (in Hungarian), *Élelmezési Ipar*, 33(8), 1979, 308-310.
7. Box, G.E.P., Hunter, W.G. and Hunter J.S.: *Statistics for Experimenters: An Introduction to Design, Data Analysis, and Model Building*, John Wiley & Sons, New York 1978
8. Kemény, S. and Deák, A.: *Planning Measurements and Evaluating their Results* (in Hungarian), Műszaki Könyvkiadó, Budapest 1990
9. Taguchi, G: *System of Experimental Design: Engineering Methods to Optimize Quality and Minimize Cost*, White Plains, NY: UNIPUB/Kraus International 1987
10. Kemény, S. and Deák, A.: Low-cost quality with Japanese method (Quality philosophy of G. Taguchi), Plenary lecture in Kemometriai Tanulmányok (Előadás kivonat), KEMOEMTRIA'93 konferencia, Balatonfüred, 1993. október 18-20.

ROTÁCIÓS FILMBEPÁRLÓ BERENDEZÉS ÉRZÉKENYSÉGÉNEK VIZSGÁLATA TAGUCHI FÉLE KÍSÉRLRTTERVEZÉSI MÓDSZERREL Összefoglalás

Rotációs filmbepárló berendezés optimalizálását végeztük el a kísérlettervezés módszertanát alkalmazva. Figyelembe vettük az előzőleg végzett kísérletek eredményeit, melyek alapján elsőfokú faktoriális tervet készítettünk és ennek eredményeit felhasználva alkottuk meg a gradiens tervet. Modell anyagként vizet használtunk, hiszen az élelmiszeriparban legtöbbször a víz eltávolítása a feladat a bepárlás során.

Az optimalizáció után a folyamatra legérzékenyebb művelettani paraméterek felderítését végeztük el a Taguchi módszerrel. Modell anyagként aszkarbinsavtartalmú cukoroldatot alkalmaztunk. Eredményeinket számos grafikon és táblázat segítségével mutatjuk be az alkalmazott matematikai statisztikai módszerek megvilágítása céljából.